

# JCH FUEL SOLUTIONS

THE LEADER IN AUTOMATED FUEL CLEANING AND MAINTENANCE SYSTEMS



The **Enviro 2** is designed to keep middle distillate fuel in main storage tanks under 2,000 gallons in a pristine state.

## ENVIRO 2

Up To  
2,000 Gal. Tanks  
Microprocessor-Based  
Time-Switch

The **Enviro 2** is a wall mounted, close looped system with leak detection and built-in diagnostics that give you healthy fuel to run your equipment and a clean storage tank at the same time.

Fully automated, UL listed control panel with a microprocessor-based time switch for ease of use and maintenance. This system monitors fuel contamination levels and alerts the user of saturation levels and maintenance needs on an LED display. For your convenience, alarms can also be interfaced with central plant monitoring. Maintenance can then be scheduled and the system brought back online.

This system was also designed to meet environmental issues for safe operation and offers complete fuel remediation and control. Detailed written specifications are available on request.

**Weight:** 150 lbs.

**Size:** 24" h x 24" w x 10" d

**Power:** 120 VAC/6.8A 50/60 HZ single

**Plumbing:** 3/4" black pipe or larger depending on length of run

**Flow Rate:** 3gpm = 180gph

### Multiple Stages of Filtration:

**Stage 1:** 100 Micron particulate and bulk water removal through a spin-on type strainer and water separator.

**Stage 2:** 10 micron particulate and 99.995% emulsified and entrained water removal through a spin-on canister type element.

**Stage 3:** 2 micron fine finish filter through a spin-on canister type element.

**Not For Use With Gasoline**